

CERTIFICATE OF COMPLIANCE

Certificate Number 20161129-E354332
Report Reference E354332-20160511
Issue Date 2016-NOVEMBER-29

Issued to: LUMENPULSE LIGHTING INC
SUITE 1505
1751 RICHARDSON ST
MONTREAL, QC H3K 1G6 CANADA

This is to certify that representative samples of LIGHT-EMITTING-DIODE RECESSED LUMINAIRES
See Addendum page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 1598 (1) & C22.2 NO 250.0-08(1), Luminaires
UL 8750, Light Emitting Diode (LED) Equipment for Use in Lighting Products;
SA C22.2 No. 250.13, Light Emitting Diode (LED) Equipment for Lighting Applications.

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20161129-E354332
Report Reference E354332-20160511
Issue Date 2016-NOVEMBER-29

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Light-Emitting-Diode, Recessed Luminaire, Type IC, SUITABLE FOR DAMP LOCATIONS:

LLI2R-120/277-Z-dRO-YYY-NO; LLI2R-120/277-Z-dHO-YYY-NO; LLI2R-120/277-Z-dRO-YYY-XXX;
LLI2R-120/277-Z-dHO-YYY-XXX; LLI2R-120/277-Z-dRO-YYY-LT; LLI2R-120/277-Z-dHO-YYY-LT;
LLI2R-Z-120/277-dRO-RGB-LT, DMX/RDM; LLI2R-120/277-Z-dRO-RD,GR,BL-NO;
LLI2R-120/277-Z-dRO-RD,GR,BL,RGBW-LT, DMX/RDM;
LLI2R-120/277-Z-dRO-DWH,DWW-LT, DMX/RDM; LLI2R-120/277-Z-dHO-DWH,DWW-LT, DMX/RDM,
LLI2R-D-347-Z-dRO-YYY-NO,LLI2R-D-347-Z-dHO-YYY-NO,LLI2R-D-347-Z-dRO-YYY-XXX,
LLI2R-D-347-Z-dHO-YYY-XXX, LLI2R-D-347-ZZ-dRO-YYY-NO,LLI2R-D-347-ZZ-dHO-YYY-NO,
LLI2R-D-347-ZZ-dRO-YYY-XXX,LLI2R-D-347-ZZ-dHO-YYY-XXX

Z = Length of Luminaire should be 1ft , 2ft 3ft, 4ft, 6ft, 7ft, 8ft

XXX = DIM, DALI, ES, DMX/RDM

YYY = 2700K, 3000K, 3500K, 4000K



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

